

GENERAL INFORMATION

Project Name: _____

STANDARD SPECIFICATIONS

- Finish: Gray
- Remote Toggle Switch
- Housing: Aluminum Extrusion

OPTIONS AND ACCESSORIES

OPTIONAL FINISHES

- Brushed Aluminum
- Gloss Black
- Wrinkle Black
- Smoked Copper
- Polished Brass
- Other: _____

OPTIONAL SWITCH

- Internal Toggle Switch

WIRING EXIT POINT OPTIONS

- Top
- Left Side
- Right Side

INFORMATION FOR LED BULB

Temperature	3000K
Average Rated Life (hr):	50,000
Color Rendering Index (CRI)	90
Diodes	50 per foot
Electrical	110-250V
Frequency	50/60Hz
Amp Per Foot @ 100V	0.04
Watts Per Foot	5
Lumens Per Foot	400

BALLAST INFORMATION - LED

HOUSING LENGTH*	MODULE LENGTH	FREQUENCY	AMPS @ 120V	AMPS @ 208V	AMPS @240V	WATTS
15"-20"	12"	50/60 Hz	0.042	0.024	0.021	5W
21"-26"	18"	50/60 Hz	0.058	0.034	0.029	7W
27"-32"	12" & 12"	50/60 Hz	0.083	0.048	0.042	10W
33"-38"	12" & 18"	50/60 Hz	0.1	0.058	0.05	12W
39"-44"	36"	50/60 Hz	0.125	0.072	0.063	15W
45"-50"	12" & 18"	50/60 Hz	0.142	0.082	0.071	17W
51"-56"	48"	50/60 Hz	0.167	0.096	0.083	20W

* Rounded up to the nearest foot.

Larger Sizes: BSI will configure bulb combinations to best fit housing.

Approval Drawings Required



01.25

2580 LED Slimline Light

