

ZGUARD® FOOD SHIELDS

GENERAL INFORMATION

Project Name:_

STANDARD NSF LISTED FINISH OPTIONS

- □ Brushed Aluminum □ Chrome
- □ Gloss Black
 □ Wrinkle Black
- □ Smoked Copper
 □ Polished Brass Finish
- Other __

GLASS THICKNESS

- 1/4" Tempered Glass (not for shelves) Centerline Max 54"
- 3/8" Tempered Glass (for shelf or span more than 54") Centerline Max 66"
- □ 1/2" Tempered Glass (for shelf or span more than 66") Centerline Max 72"

GLASS CORNERS

- □ 1" Radius Corner (standard)
- Square Corners


LIGHT OPTIONS


□ 2580 Slimline LED Light

For warmers contact BSI factory.

All BSI light units are UL Listed. See light spec sheets for detailed information. Also available with other manufacturers' light units. Contact BSI for details.

ZG9915 Combo-Serve





To meet NSF guidelines, end panels are included on all BSI quotations unless specifically excluded. (See end panel page for more details).

INSTALLATION OPTIONS

Above Counter: Stainless Steel Counter	□ SS1: EZ Mount 2" x 8" Flange
Under Counter: Stainless Steel Counter	□ SSU3-H: Heavy-Duty Flange
(Requires Under Counter Reinforcement & Access)	□ SSU3-N: Narrow Flange
	□ SSU5-H: Heavy-Duty Flange
	□ SSU5-N: Narrow Flange
Above-Counter: Millwork Counter	□ MW1: Heavy-Duty Flange
	□ MW2: Narrow Flange
Under-Counter: Millwork Counter	□ MWU3: Narrow Flange
	MWU4: Compression Installation (not recommended for solid surfaces)
	□ MWU5: Heavy-Duty Flange

Approval Drawings Required. Specifications subject to change without notice.



